

# Mabanol Radon Gear ATF 8 Speed

## High Performance Automatic Transmission Fluid

### Application

Mabanol Radon Gear ATF 8 Speed is a high-performance automatic transmission fluid perfectly suited to be used in ZF 8HP transmissions, most notably 8HP45, 8HP55, 8HP70 und 8HP90.

It can also be used in a number of ZF 6HP transmissions often found in models of Volkswagen AG.

### Recommended for

- BMW 8322 2152426/2289720 (ATF 3+)
- Chrysler 68157995AA
- Fiat 9.55550-AV5
- Jaguar 02 JDE 26444
- Land Rover LR023288
- VAG G-060-162

### Properties

Mabanol Radon Gear ATF 8 Speed's formulation brings together high-quality synthetic base stocks with a suitable additive package.

It meets stringent fuel economy standards by virtue of its low viscosity grade. Further to the above it offers various extraordinary attributes which include very good thermal properties, a very low pourpoint as well as resistance against vibration. It provides protection against wear, corrosion and oxidation, thus ensuring a smooth driving experience and longest lifetime.

Mabanol Radon Gear ATF 8 Speed is dyed green.

### Data

	Unit	Value
Density at 15°C	g/cm <sup>3</sup>	0,842
Kin. Viscosity at 40°C	mm <sup>2</sup> /s	25,80
Kin. Viscosity at 100°C	mm <sup>2</sup> /s	6,00
Viscosity Index		190
Flash point COC	°C	198
Pourpoint	°C	-45

Updated in January 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1987