

## Mabanol Radon Gear GL 4 75W-90

### Multipurpose Gear Oil

#### Application

Mabanol Radon Gear GL 4 75W-90 is suitable for use in heavily-loaded synchronous and asynchronous manual transmissions, transfer box gears and steering gears in vehicles.

#### Properties

By virtue of its formulation which is comprised of mineral oil and synthetic components, Mabanol Radon Gear GL 4 75W-90 offers extraordinary oxidation stability, excellent low temperature properties as well as very good viscosity-temperature attributes and a high shear stability.

#### Specifications

- SAE Grade 75W-90
- API GL-4

#### Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm <sup>3</sup>	0,877
Dyn. Viscosity at -40°C	ASTM D 5293	mPa s	95.000
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm <sup>2</sup> /s	75,8
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm <sup>2</sup> /s	13,7
Viscosity Index (VI)	DIN ISO 2909		190
Flashpoint COC	DIN ISO 2592	°C	210
Pourpoint	DIN ISO 3016	°C	-45

Updated in August 2016

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1987