

## Mabanol Radon Gear XHP GL 4 75W-80

Synthetic High-Performance Fuel Economy Gear Oil

### Application

Mabanol Radon Gear XHP GL 4 75W-80 is a high-performance gear oil designed for use in heavily loaded manual transmissions. The fuel economy formulation significantly reduces maintenance costs and leads to increased profitability as well as oil change intervals of up to 500.000 km.

### Properties

Mabanol Radon Gear XHP GL 4 75W-80 is a synthetic fuel-economy gear oil. Synthetic base oils coupled with an innovative additive package ensure that the latest industry requirements are fully met.

Mabanol Radon Gear XHP GL 4 75W-80 provides exceptional protection against mechanical and thermal loads even at extended oil drain intervals.

### Specifications

- SAE Grade 75W-80
- API GL-4

### Approval

- MAN 341 Type Z4

### Recommended for

- DAF
- Iveco 18-1807-MGS1
- Renault
- Voith Oil Class C
- Volvo 97305
- ZF TE-ML 01L / 02D / 02L 07A / 08 / 16K

### Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm <sup>3</sup>	0,863
Kin. Viscosity at 40°C	DIN 51562/T1	mm <sup>2</sup> /s	75,3
Kin. Viscosity at 100°C	DIN 51562/T1	mm <sup>2</sup> /s	11,7
Viscosity Index (VI)			149
Flashpoint COC	DIN ISO 2592	°C	220
Pourpoint	DIN ISO 3016	°C	<-42

Updated in June 2021

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1987